Songman®

VV_HUNTER®

GAMING

2022 CATALOGUE











Dongguan Songman Technology Company Limited is one of the most professional manufacturer and supplier of gaming products, located in Dongguan city, since 2009. We offer OEM business service for our good clients.

With more than ten years development, we have rich experience in researching, designing and manufacturing gaming products, especially for gaming headsets, we also applied for design patent for our main products.

Focus on unique research and design, we keep releasing newest unique design products to fulfill markets' requirement.

Compliance with BSCI and ISO 9001:2015, we have the completely management system from product design, tooling processing, hardware stamping, molding injection, assembling and packing. We also make one hundred percent full inspection before packing and shipment to ensure quality.

Applies automatic wire drawing machine, automatic high-speed hardware stamping machine, automatic injection molding machine, several assembly and packing lines, we can achieve daily output of more than ten thousand sets.

Today our products are selling not only in domestic market, but also sold to other countries in North and south America, Europe, Middle East and Asia.

As the reputable manufacturer and reliable supplier, we also try our best to supply the best business service, such as delivering the goods on time, the satisfied after-sales service.

Please don't hesitate to contact us for our good business cooperation.



CE/ROHS/FCC/Ca65 Certificates



Gaming Headsets CE



Gaming Mouses CE



Gaming Keyboards RoHS



Gaming Headsets ROHS



Gaming Mouses RoHS



The control of the state of the

Gaming Headsets FCC



Gaming Keyboards CE



BSCI ISO9001: 2015

MIC arm up / down to turn off/on MIC 2 circle LED lights





G800

Speaker Drivers

Dimensions: 50mm Impedance: 32Ω Sensitivity: 105dB±3dB Freq.Response: 20-20KHz Max.Input power: 100mW Cord length: 2.1M PC Plug type: 3.5mm x 2 + USB 7.1 Plug type: 1 x USB

Microphone

Dimensions: Φ4.0 x 1.5mm Directivity: Omnidirectional Sensitivity: -48dB±3dB Freq.Response: 50-10KHz













Half-hidden light design

Noise cancelling microphone Volume control Extended durability nylon cord





G610

Speaker Drivers

Dimensions: 50mm Impedance: 32Ω Sensitivity: 105dB±3dB Freq.Response: 20-20KHz Max.Input power: 100mW Cord length: 2.1M PC Plug type: 3.5mm x 2 + USB 7.1 Plug type: 1 x USB

Microphone

Dimensions: Φ4.0 x 1.5mm Directivity: Omnidirectional Sensitivity: -48dB±3dB Freq.Response: 50-10KHz











Noise cancelling microphone Volume control

Extended durability nylon cord Auto-adjusting metal headband





G900

Speaker Drivers

Dimensions: 50mm Impedance: 32Ω Sensitivity: 105dB±3dB Freq.Response: 20-20KHz Max.Input power: 100mW Cord length: 2.1M PC Plug type: 3.5mm x 2 + USB 7.1 Plug type: 1 x USB

Microphone

Dimensions: Φ4.0 x 1.5mm Directivity: Omnidirectional Sensitivity: -48dB±3dB Freq.Response: 50-10KHz

7.1 Channel Built-In Sound Card













2.4G & 5.8G Wireless+ RGB light+Bluetooth

Fashion Model Design
Perfect Sound output
High-end Tire-Style earn

High-end Tire-Style earpads Long time playing













Transmitter

G810W

Speaker Drivers

Dimensions: 50mm Impedance: 320 Sensitivity: 105dB±3dB Freq.Response: 20-20KHz Max.Input power: 100mW Operating voltage: 3.3-4.2V Operating current: 50mA Battery capacity: 500mAh Play time: 8hrs Charging time: 2.5hrs Freq.range: 2.400-5.800Ghz SNR: 75dB

Microphone

Dimensions: Φ4.0 x 1.5mm Directivity: Omnidirectional Sensitivity: -48dB±3dB Freq.Response: 50-10KHz

Microphone

Operating voltage: 5V Operating current: 40mA Freq.range: 2.400-2.480GHz Operating distance: ≥10M, 360° Receive sensitivity: -85dB













Big metal headband **Big-earpad for NC function**











G810





Speaker Drivers

Dimensions: 50mm Impedance: 320 Sensitivity: 105dB±3dB Freq.Response: 20-20KHz Max.Input power: 100mW Cord length: 2.1M PC Plug type: 3.5mm x 2 + USB 7.1 Plug type: 1 x USB

Microphone

Dimensions: Φ4.0 x 1.5mm Directivity: Omnidirectional Sensitivity: -48dB±3dB Freg.Response: 50-10KHz











2.4G & 5.8G Wireless+Bluetooth



G700W







Speaker Drivers

Dimensions: 50mm Impedance: 320 Sensitivity: 105dB±3dB Freq.Response: 20-20KHz Max.Input power: 100mW Operating voltage: 3.3-4.2V Operating current: 50mA Battery capacity: 500mAh Play time: 8hrs Charging time: 2.5hrs Freq.range: 2.400-5.800Ghz SNR: 75dB

Microphone

Dimensions: Φ4.0 x 1.5mm Directivity: Omnidirectional Sensitivity: -48dB±3dB Freq.Response: 50-10KHz

Microphone

Operating voltage: 5V Operating current: 40mA Freq.range: 2.400-2.480GHz Operating distance: ≥10M, 360° Receive sensitivity. -85dB













G700





Speaker Drivers

Dimensions: 50mm Impedance: 32Ω Sensitivity: 105dB±3dB Freq.Response: 20-20KHz Max.Input power: 100mW Cord length: 2.1 M PC Plug type: 3.5mm x 2 + USB 7.1 Plug type: 1 x USB

Microphone

Dimensions: Φ4.0 x 1.5mm Directivity: Omnidirectional Sensitivity: -48dB±3dB Freq.Response: 50-10KHz

















G780

Speaker Drivers

Dimensions: 50mm Impedance: 32Ω Sensitivity: 105dB±3dB Freq.Response: 20-20KHz Max.Input power: 100mW Cord length: 2.1M PC Plug type: 3.5mm x 2 + USB 7.1 Plug type: 1 x USB

Microphone

Dimensions: Φ4.0 x 1.5mm Directivity: Omnidirectional Sensitivity: -48dB±3dB Freq.Response: 50-10KHz



















G790

Speaker Drivers

Dimensions: 50mm Impedance: 320 Sensitivity: 105dB±3dB Freq.Response: 20-20KHz Max.Input power: 100mW Cord length: 2.1M PC Plug type: 3.5mm x 2 + USB 7.1 Plug type: 1 x USB

Microphone

Dimensions: Φ4.0 x 1.5mm Directivity: Omnidirectional Sensitivity: -48dB±3dB Freq.Response: 50-10KHz











Detachable Microphone

Noise cancelling microphone Volume control Extended durability nylon cord Auto-adjusting metal headband





G650



Dimensions: 50mm Impedance: 32Ω Sensitivity: 105dB±3dB Freq.Response: 20-20KHz Max.Imput power: 100mW Cord length: 2.1M Cord length: 2.1M 2+ USB 7.1 Plug type: 1 x USB

Microphone

Dimensions: Φ4.0 x 1.5mm Directivity: Omnidirectional Sensitivity: -48dB±3dB Freq.Response: 50-10KHz

















G750



Dimensions: $\Phi4.0 \times 1.5$ mm Directivity: Omnidirectional Sensitivity: -48dB±3dB Freq.Response: 50-10KHz



Sensitivity: 105dB±3dB Freq.Response: 20-20KHz Max.linput power: 100mW Cord length: 2.1M PC Plug type: 3.5mm x 2 + USB 7.1 Plug type: 1 x USB

Speaker Drivers

Dimensions: 50mm

Impedance: 320













9 in 1 LED lights:

RGB rainbow + RGB flow + 7 colors in one headset **LED MODES:**

Switch RGB rainbow to RGB flow to 7 colors on button





G600







Speaker Drivers

Dimensions: 50mm Impedance: 320 Sensitivity: 105dB±3dB Freq.Response: 20-20KHz Max.Input power: 100mW Cord length: 2.1M PC Plug type: 3.5mm x 2 + USB 7.1 Plug type: 1 x USB

Microphone

Dimensions: Φ4.0 x 1.5mm Directivity: Omnidirectional Sensitivity: -48dB±3dB Freg.Response: 50-10KHz











9 in 1 LED lights:

RGB rainbow + RGB flow + 7 colors in one headset LED MODES:

Switch RGB rainbow to RGB flow to 7 colors on button





G500

Speaker Drivers

Dimensions: 50mm Impedance: 32Ω Sensitivity: 105dB±3dB Freq.Response: 20-20KHz Max.Input power: 100mW Cord length: 2.1M PC Plug type: 3.5mm x 2 + USB 7.1 Plug type: 1 x USB

Microphone

Dimensions: Φ4.0 x 1.5mm Directivity: Omnidirectional Sensitivity: -48dB±3dB Freq.Response: 50-10KHz


















Noise cancelling microphone Volume control







G300

Speaker Drivers

Dimensions: 50mm Impedance: 32Ω Sensitivity: 105dB±3dB Freq.Response: 20-20KHz Max.Input power: 100mW Cord length: 2.1M PC Plug type: 3.5mm x 2 + USB 7.1 Plug type: 1 x USB

Microphone

Dimensions: Φ4.0 x 1.5mm Directivity: Omnidirectional Sensitivity: -48dB±3dB Freq.Response: 50-10KHz













9 in 1 LED lights:

RGB rainbow + RGB flow + 7 colors in one headset LED MODES:

Switch RGB rainbow to RGB flow to 7 colors on button





G550

Speaker Drivers

Dimensions: 50mm Impedance: 32Ω Sensitivity: 105dB±3dB Freq.Response: 20-20KHz Max.Input power: 100mW Cord length: 2.1 M PC Plug type: 3.5mm x 2 + USB 7.1 Plug type: 1 x USB

Microphone

Dimensions: Φ4.0 x 1.5mm Directivity: Omnidirectional Sensitivity: -48dB±3dB Freq.Response: 50-10KHz







7.1 Channel Built-In Sound Card













Noise cancelling microphone Volume control Extended durability nylon cord Auto-adjusting metal headband





G200

Speaker Drivers

Dimensions: 50mm Impedance: 320 Sensitivity: 105dB±3dB Freq.Response: 20-20KHz Max.Input power: 100mW Cord length: 2.1M PC Plug type: 3.5mm x 2 + USB 7.1 Plug type: 1 x USB

Microphone

Dimensions: Φ4.0 x 1.5mm Directivity: Omnidirectional Sensitivity: -48dB±3dB Freg.Response: 50-10KHz















G100

Speaker Drivers

Dimensions: 50mm Impedance: 32Ω Sensitivity: 105dB±3dB Freq.Response: 20-20KHz Max.Input power: 100mW Cord length: 2.1M PC Plug type: 3.5mm x 2 + USB 7.1 Plug type: 1 x USB

Microphone

Dimensions: Φ4.0 x 1.5mm Directivity: Omnidirectional Sensitivity: -48dB±3dB Freq.Response: 50-10KHz

















V100

Keys: 104
Switch type:mechanical(ABT Blue)
Switch rating:≥50 million presses
Key route: 3.8±0.2mm
Operating force: 60±5g
Backlight: RGB
Interface: USB 2.0
Cable length: 1.75m
OS Support: Windows 7 or newer













V200

Keys: 104
Switch type:mechanical(ABT Blue)
Switch rating:≥50 million presses
Key route: 3.8±0.2mm
Operating force: 60±5g
Backlight: RGB
Interface: USB 2.0
Cable length: 1.75m
OS Support: Windows 7 or newer







3 Modes:

2.4G+Bluetooth+Detachable Wired

Stylish design
Double colors injection
Key stoke 2.0MM
50 million switch life span
Backlights for key caps and gaps











V300/V300W

Keys: 104
Switch type:mechanical(ABT Blue)
Switch rating:≥50 million presses
Key route: 3.8±0.2mm
Operating force: 60±5g
Backlight: RGB
Interface: USB 2.0
Cable length: 1.75m
OS Support: Windows 7 or newer













K311



Keys:104
Switch type:mechanical(ABT Blue)
Switch rating:≥50 million presses
Key route: 3.8±0.2mm
Operating force: 60±5g
Backlight: RGB
Interface: USB 2.0
Cable length: 1.75m
OS Support: Windows 7 or newer













K320

Keys:104
Switch type:mechanical(ABT Blue)
Switch rating:≥50 million presses
Key route: 3.8±0.2mm
Operating force: 60±5g
Backlight: RCB
Interface: USB 2.0
Cable length: 1.75m
OS Support: Windows 7 or newer







3 Modes:

2.4G+Bluetooth+Detachable Wired

Stylish design
Double colors injection
Key stoke 2.0MM
50 million switch life span
Backlights for key caps and gaps











K321/K321W

Keys:104
Switch type:mechanical(ABT Blue)
Switch rating:≥50 million presses
Key route: 3.8±0.2mm
Operating force: 60±5g
Backlight: RGB
Interface: USB 2.0
Cable length: 1.75m
OS Support: Windows 7 or newer













K330

Keys:61
Switch type:mechanical(ABT Blue)
Switch rating:≥50 million presses
Key route: 3.8±0.2mm
Operating force: 60±5g
Backlight: RGB
Interface: USB 2.0
Cable length: 1.75m
OS Support: Windows 7 or newer













K340

Keys:61
Switch type:mechanical(ABT Blue)
Switch rating:≥50 million presses
Key route: 3.8±0.2mm
Operating force: 60±5g
Backlight: RGB
Interface: USB 2.0
Cable length: 1.75m
OS Support: Windows 7 or newer















Keys:104
Switch type:mechanical(ABT Blue)
Switch rating:≥50 million presses
Key route: 3.8±0.2mm
Operating force: 60±5g
Backlight: RGB
Interface: USB 2.0
Cable length: 1.75m
OS Support: Windows 7 or newer















K360

Keys:68
Switch type:mechanical(ABT Blue)
Switch rating:≥50 million presses
Key route: 3.8±0.2mm
Operating force: 60±5g
Backlight: RGB
Interface: USB 2.0
Cable length: 1.75m
OS Support: Windows 7 or newer













K371

Keys:104
Switch type:mechanical(ABT Blue)
Switch rating:≥50 million presses
Key route: 3.8±0.2mm
Operating force: 60±5g
Backlight: RGB
Interface: USB 2.0
Cable length: 1.75m
OS Support: Windows 7 or newer









Specifications

Sensor: Optical,PAN3325

DPI:1000-2000-3000-4000-6000-8000

Buttons:7

Switch rating: 10 million clicks

Backlight:RGB Interface:USB 2.0 Cable Length:1.8m











Specifications

Sensor: Optical, PAN3325

DPI:1000-2000-3000-4000-6000-8000

Buttons:7

Switch rating: 10 million clicks

Backlight:RGB Interface:USB 2.0 Cable Length:1.8m











Specifications

Sensor: Optical,PAN3325

DPI:1000-2000-3000-4000-6000-8000

Buttons:7

Switch rating: 10 million clicks

Backlight:RGB Interface:USB 2.0 Cable Length:1.8m













Specifications

Sensor: Optical, PAN3325

DPI:1000-2000-3000-4000-6000-8000

Buttons:7

Switch rating: 10 million clicks

Backlight:RGB Interface:USB 2.0 Cable Length:1.8m











Specifications

Sensor: Optical, PAN3325

DPI:1000-2000-3000-4000-6000-8000

Buttons:7

Switch rating: 10 million clicks

Backlight:RGB Interface:USB 2.0 Cable Length:1.8m











Specifications

Sensor: Optical, PAN3325

DPI:1000-2000-3000-4000-6000-8000

Buttons:7

Switch rating: 10 million clicks

Backlight:RGB Interface:USB 2.0 Cable Length:1.8m











Specifications

Sensor: Optical, PAN3325

DPI:1000-2000-3000-4000-6000-8000

Buttons:7

Switch rating: 10 million clicks

Backlight:RGB Interface:USB 2.0 Cable Length:1.8m











Specifications

Sensor: Optical,PAN3325

DPI:1000-2000-3000-4000-6000-8000

Buttons:7

Switch rating: 10 million clicks

Backlight:RGB Interface:USB 2.0 Cable Length:1.8m











Specifications

Sensor: Optical, PAN3325

DPI:1000-2000-3000-4000-6000-8000

Buttons:7

Switch rating: 10 million clicks

Backlight:RGB Interface:USB 2.0 Cable Length:1.8m













Specifications

Sensor: Optical, PAN3325

DPI:1000-2000-3000-4000-6000-8000

Buttons:7

Switch rating: 10 million clicks

Backlight:RGB Interface:USB 2.0 Cable Length:1.8m









Gaming here Happy here!

ADD

Building E, 2nd Rd., Fulong 2nd Industrial Park, Shipai Town, Dongguan City, Guangdong Province, China 523 349

EMAIL

sales@songman-china.com

TEL

+86-769-8278 0755

FAX

+86-769-8278 0756

Dongguan Songman Technology Co., LTD.

www.songman-china.com www.vvhunter.com



Scan Wechat